



- 1. SIGNAGE TO BE CONFIRMED AT DETAILED DESIGN STAGE ALL ROAD SIGNAGE TO COMPLY WITH THE DEPARTMENT OF TRANSPORT TRAFFIC SIGNS MANUAL
- 2. SIGN POLES MAX. DIAMETER 89mm. WHERE PEDESTRIANS ARE LIKELY TO WALK UNDER THE SIGN, THE DESIRABLE MOUNTING HEIGHT IS 2300mm. WHERE CYCLISTS ARE LIKELY TO PASS UNDER THE SIGN, THE DESIRABLE MOUNTING HEIGHT IS 2500mm
- 3. RETENTION SOCKETS TO BE USED ON ALL SIGN POLES
- 4. ALL ROAD SIGNAGE TO BE AGREED WITH THE LOCAL AUTHORITY
- LOCATION OF SIGNAGE TO BE AGREED, ON SITE, WITH THE LOCAL AUTHORITY BEFORE ERECTING.
- 6. REFER TO DRAWINGS FOR LOCATIONS OF TACTILE PAVING
- 7. PROPOSED BESPOKE LEFT-TURN YIELD SIGNAGE

EXISTING TOPOGRAPHICAL SURVEY TAKEN FROM DRAWINGS 22-382-01 to 18 (DATED 08-12-2022)

© PUNCH Consulting Engineers

This drawing and any design hereon is the copyright of the Consultants and must not be reproduced without their written consent. All drawings remain the property of the Consultants. Figured dimension only to be taken from this drawing. Consultants to be informed immediately of any discrepancies before work proceeds.













Dublin | Limerick | Cork | Galway | Glasgow

97 Henry Street, Limerick, V94 YC2H t +353 61 221 200 | w punchconsulting.com

SOUTH CIRCULAR ROAD TO BISHOPS QUAY CYCLE SCHEME

AMENDMENT 2 - SIGNALISATION OF BALLINACURRA/LIFFORD AVE. S Buckley December 2022 J Tiernan 211101-PUNCH-02-XX-M2-C-0421-0426 211101 Scale @ A3: 1:500 211101-PUNCH-02-XX-DR-C-0422 C03